



Designed for offshore fishing enthusiasts,

the Fishfinder 100 Blue and Fishfinder

160 Blue operate at dual frequencies.

With the 50/200 kHz transducer, you can

reach greater depths and get a wider

Fishfinders suited for the deep blue open seas

viewing area. And you will see those

returns on a crisp, four-level grayscale

screen for excellent separation and

contrast. These seaworthy fishfinders are

rugged and waterproof. But despite their

tough exterior, they are extremely easy to

operate, with features like a convenient

adjustment bar that gives you access to

the most commonly used fishing settings.



Fishfinder Blue Series specifications

Features

- Display options:** Auto ranging, 2X and 4X auto and manual zoom, 3 Fish Symbol™ sizes, adjustment bar
- Alarms:** Deep water alarm, shallow water alarm, 3 size fish alarm, battery low alarm
- Transducer auto-sense:** Automatically displays speed and temp data without menus
- See-Thru® technology:** Shows weak/strong returns simultaneously
- Depth Control Gain (DCG®):** Automatically adjusts fishfinder sensitivity according to depth
- Power down backup of settings:** Customer settings not lost when unit is turned off

Physical

- Case:** Fully gasketed, high-impact plastic alloy
- Keys:** Backlighted
- Temperature range:** 5°F to 158°F (-15°C to 70°C)
- Waterproof:** IEC 529, level IPX-7
Submerged to 1 meter for 30 minutes

Accessories

- Standard:** Flush mount or surface mount with knobs
Wiring adapter cable
Transom mount transducer with depth and temp*
Speed sensor (standard on Fishfinder 160 Blue)
User's manual
Protective front cover (standard on Fishfinder 160 Blue)
- Optional:** Second mounting kit
Quick-release flush mounting kit
- Optional Transducers:** Trolling motor mount adapter
Plastic transom mount with depth/temp
Speed sensor
Bronze thru-hull with depth/temp
Bronze thru-hull with depth/speed/temp
Plastic thru-hull with depth
In-hull
Temperature sensor
Suction cup adapter

Here's how the units are different

Fishfinder 100 Blue



Fishfinder 160 Blue



	Fishfinder 100 Blue	Fishfinder 160 Blue
display	100 W x 160 H pixels 3.9" diagonal (9.9 cm) 2" x 3.3" (5 x 8.3 cm) FSTN LCD with amber LED backlighting	160 W x 160 H pixels 4.6" diagonal (11.7 cm) 3.3" x 3.3" (8.3 x 8.3 cm) FSTN LCD with incandescent backlighting
sonar power output	300 watts (RMS) 2400 watts (peak to peak)	500 watts (RMS) 4000 watts (peak to peak)
frequency	50/200 kHz (40°/10°)	50/200 kHz (40°/10°)
depth	1200 foot max depth**	1500 foot max depth**
power usage	7 watts max	12 watts max
size	4.9"H x 5.3"W x 2.7"D (12.5 x 13.5 x 6.9 cm)	4.93"H x 6.3"W x 3.0"D (12.5 x 16 x 7.6 cm)
weight	13 oz.	1 lb. 6 oz.
temperature	standard	standard

©2000 GARMIN Corporation



GARMIN (Asia) Corporation
No. 68, Jangshu 2nd Rd.
Shijr, Taipei County, Taiwan
886/2.2642.9199 fax 886/2.2642.9099

GARMIN International
1200 East 151st Street
Olathe, Kansas 66062, U.S.A.
913/397.8200 fax 913/397.8282

GARMIN (Europe) Ltd.
Unit 5, The Quadrangle
Abbey Park Industrial Estate
Romsey, SO51 9AQ, U.K.
44/1794.519944 fax 44/1794.519222

www.garmin.com

Specifications are preliminary and subject to change without notice.

* Also available without transducer

**Depth capacity is dependent on water salinity, bottom type, and other water conditions.