

ICOM

VHF AND UHF TRANSCEIVERS

IC-F1010
IC-F2010



The photo shows actual size.



Icom Inc

ADDITIONAL FEATURES

- Selectable channel spacing (channel independent)
- 32 channels for 5-tone encoder (standard)
- Emergency call with single or repeat function
- 8 identities + group code for 5-tone decode (optional)
- Selectable digits for 5-tone decoded indication
- Automatic ID transmission linked to PTT
- Standard CTCSS with 51 frequencies (plus 1 programmable)
- Standard DTCS with selectable polarity
- 7 DTMF autodialing memories
- Up to 8 characters for memory name indication
- Bank separation capability
- 5 scan channel groups
- 2 priority channels
- Automatic scan start and/or receive mute when mic is replaced in the hanger
- Automatic priority channel selection and/or receive mute release when mic is picked up
- Normal scan and priority scan
- Power ON scan start
- Adjustable transmit release period to prevent noise burst at end of transmission when using CTCSS
- Remote monitoring capability (optional UT-96 required)
- Optional passcode input to prevent operation by unauthorised persons
- Programmable minimum level for audio
- Selectable transmit power
- Talk around function (temporary simplex operation on a duplex channel)
- Time-out timer
- Time-out ID transmission
- Penalty timer
- Transmit lockout (channel busy/repeater/reverse repeater)
- 2 selectable 'stun' functions (optional UT-96 required)
- External I/O terminal socket (optional OPC-617 required)

SPECIFICATIONS

GENERAL

- Frequency coverage

IC-F1010	: 136-155 MHz
	146-174 MHz
IC-F2010	: 400-430 MHz
	450-490 MHz
	490-520 MHz
- Mode : 16K0F3E, 8K50F3E
- No. of channels : 32 (standard), 160 (optional)
- Channel spacing : 12.5 kHz and 25 kHz
- Power supply : 13.2 V DC \pm 15% requirement (negative ground)
- Current drain (at 13.2 V DC)

High	7 A (IC-F1010)	8 A (IC-F2010)
Low	3 A (IC-F1010)	4 A (IC-F2010)

 Squelched 700 mA
Max. audio output 1.2 A

- Usable temp. range : -25°C to +55°C
- Frequency stability : \pm 1500 Hz
- Dimensions : 150(W) x 50(H) x 180(D) mm (proj. not included)
- Weight : 1.5 kg

TRANSMITTER

- Output power : High 25 W
Low 2.5 W
- Max. frequency deviation : \pm 2.5 kHz, \pm 5.0 kHz
- Adjacent channel power : 60 dB (12.5 kHz)
70 dB (25 kHz)
- Spurious emissions : 0.25 μ W (max.)
- Hum and noise : 50 dB typ. (IC-F1010)
45 dB typ. (IC-F2010)



RECEIVER

- Sensitivity : 0.63 μ V emf (IC-F1010)
(20 dB SINAD) 0.67 μ V emf (IC-F2010)
- Squelch sensitivity : 0.22 μ V (IC-F1010)
(at threshold) 0.25 μ V (IC-F2010)
- Adj. channel selectivity : 70 dB typ. (12.5 kHz)
75 dB typ. (25 kHz)
- Intermodulation rejection : 65 dB
- Spurious response rejection (typical) : 80 dB (IC-F1010)
70 dB (IC-F2010)
- Hum and noise (typical) : 50 dB (IC-F1010)
45 dB (IC-F2010)
- Audio output power : 4 W typ. at 10% distortion
with a 4 Ω load

Measurements made in accordance with ETS-300-086. All stated specifications are subject to change without notice or obligation.

OPTIONS

- **EX-1761** MEMORY EXPANSION UNIT
- **OPC-617** ACC CABLE
For external terminal connection.
- **RMK-1** SEPARATION KIT + **OPC-609** SEPARATION CABLE
For front panel detachment installation (1.9 m).
- **SP-5** EXTERNAL SPEAKER
Large speaker for good audio quality.
Input impedance: 4 Ω ; Max. input power: 5 W.
- **SP-10** EXTERNAL SPEAKER
Compact and easy-to-install.
Input impedance: 4 Ω ; Max. input power: 5 W.
- **UT-96** 5-TONE UNIT
Provides the transceiver with 5-tone decoder capabilities.
- **UT-105** SmarTrunk II™ Logic Board*
Provides SmarTrunk II™ capabilities.
*SmarTrunk II™ is a trademark of SmarTrunk Systems



Icom Inc. 6-9-16, Kamihigashi, Hirano-ku, Osaka 547, Japan Phone: 06 793 5302 Fax: 06 793 0013

Count on us!

Icom America Inc.

<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
Telex: 152210 ICOM AMER BVUE

<Customer Service>
Phone: (425) 454-7619

Icom Canada

A Division of Icom America Inc.
3071 #5 Road, Unit 9, Richmond, B.C., V6X 2T4, Canada
Phone: (604) 273-7400 Fax: (604) 273-1900

Icom (Australia) Pty. Ltd.

A.C.N. 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0022

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 333639

Icom Telecomunicaciones S.I.

"Edificio Can Castanyer" Crta. Gracia a Manresa km. 14,750
08190 Sant Cugat Del Valles Barcelona, SPAIN
Phone: (3) 589 46 82 Fax: (3) 589 04 46

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
Telex: 317210 BUREAU G

Icom France S.a

Zac de la Plaine, Rue Brindejonc des Moulinais
BP 5804, 31505 Toulouse Cedex, France
Phone: 561 36 03 03 Fax: 561 36 03 00
Telex: 521515 ICOM FRA

Your local distributor/dealer: