


IC-M45 IC-M45EURO

Easy, reliable operation!

Flush-mount design and superior construction

Because the marine environment can be very unforgiving, the IC-M45 is designed to provide communications you can rely on under the most demanding of conditions. Water-resistant gaskets are used throughout, including the microphone, to prevent water intrusion. A durable, one piece aluminum die-cast chassis provides dependability and good heat dispersal for stable transmissions. In addition, flush mounting* into an instrument control panel or similar flat surface is a snap with the newly designed mounting 'lip.'

*An optional MB-69 FLUSH MOUNT KIT is required.

Simple operation

Operating the IC-M45 couldn't be easier. Controls and switches are clearly labelled, providing intuitive operation—even for beginners. A large, easy-to-read display measuring 20(H)×60(W) mm* indicates all necessary information at a glance. With adjustable backlighting you can be sure to read the display under varying light conditions, including nighttime operation.

*0.79(H)×2.36(W) in.

'Tag' scan system

The 'tag' scan system makes scanning easy—simply add or delete channels at the push of a switch.

Remote function microphone

The microphone allows you to conveniently change channels or select output power without touching the front panel switches.

Dual and tri-watch functions

Features often found on radios costing much more are standard on the IC-M45. Dual and tri-watch functions provide a convenient way to monitor channel 16 (or channel 16 and the call channel) while operating on another channel.

And more...

- All international, USA and Canadian channels are available
- Weather channels with weather alert function
- Instant access to channel 16 and the call channel
- Simple up/down keys for channel selection
- Low battery indicator

Icom Inc.

SPECIFICATIONS

GENERAL

- Frequency range : Tx 156.025–157.425 MHz
Rx 156.025–163.275 MHz
- Usable channels :
All USA, international and Canadian channels; plus 10 weather channels
- Mode : FM (16K0G3E)
- Power supply : 13.8 V DC ±15%
- Current drain (at 13.8 V DC):
Tx at 25 W Less than 6 A
Rx max. audio Less than 1.2 A
- Usable temperature range:
–20°C to +60°C
–4°F to +140°F
- Antenna connector: SO-239 (50 Ω)
- Weight : 0.9 kg; 2 lb

TRANSMITTER

- Output power : High 25 W
(at 13.8 V) Low 1 W
- Modulation system:
Variable reactance phase modulation
- Spurious emissions: Less than –70 dB
- Adj. channel power: 60 dB

RECEIVER

- Receive system :
Double conversion superheterodyne
- Intermediate freq. : 1st 30.85 MHz
2nd 450 kHz
- Sensitivity : 0.22 μV typical
at 12 dB SINAD
- Squelch sensitivity: 0.22 μV typical
- Adj. ch. selectivity : 70 dB typical
- Spurious response rejection ratio:
70 dB typical
- Intermodulation rejection ratio:
70 dB typical
- Audio output power (at 13.8 V DC; 10% distortion):
4.0 W typical with a 4 Ω load
- Audio output impedance: 4 Ω

The IC-M45/EURO meets MIL-STD requirements and strict environmental standard for shock (MIL 810 C, D, E) and vibration (MIL 810 C, D, E).

All stated specifications are subject to change without notice or obligation.


Flush mounting example



OPTIONS

Type approval for options varies between countries. Ask your Dealer which options are available in your area.

- **SP-5 EXTERNAL SPEAKER**
A large, external speaker for superior audio output.
- **SP-10 EXTERNAL SPEAKER**
A compact, external speaker. Features easy installation.
- **MB-69 FLUSH MOUNT KIT**
For flush-mounting the IC-M45 to a flat surface such as an instrument control panel.
- **HM-117B/W HAND MICROPHONE** (for IC-M45EURO)
- **HM-124B/W HAND MICROPHONE** (for IC-M45)
White and black are available. Same as supplied.



Icom Inc. 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.
<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509
URL : <http://www.icomamerica.com>
<Customer Service> Phone: +1 (425) 454-7619

Icom Canada
Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090
URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.
A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: +61 (03) 9387 0666 Fax: +61 (03) 9387 0022
URL : <http://www.icom.net.au>

Icom New Zealand
146A Harris Road, East Tamaki, Auckland, New Zealand
Phone: +64 (09) 274 4062 Fax: +64 (09) 274 4708
URL : <http://www.icom.co.nz>

Icom (Europe) GmbH
Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: +49 (0211) 346047 Fax: +49 (0211) 333639
URL : <http://www.icomeurope.com>

Icom Spain S.L.
Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, Spain
Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46
URL : <http://www.icomspain.com>

Icom (UK) Ltd.
Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: +44 (01227) 741741 Fax: +44 (01227) 741742
URL : <http://www.icomuk.co.uk>

Icom France S.a
Zac de la Plaine, 1, Rue Brindejonc des Moulinais
BP 5804, 31505 Toulouse Cedex, France
Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00
URL : <http://www.icom-france.com>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899 Fax: +886 (02) 2559 1874
URL : <http://www.asia-icom.com>

Beijing Icom Ltd.
1305, Wanshang Plaza, Shijingshan Road, Beijing, China
Phone: +86 (010) 6866 6337 Fax: +86 (010) 6866 3553
URL : <http://www.bjicom.com>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.

Your local distributor/dealer: